

SENSOR CATHETER HAVING REDUCED CROSS-TALK WIRING  
ARRANGEMENTS

Reference to Related Applications

[0001] This application claims the benefit of U.S. provisional patent application Serial No. 60/413,267, filed September 23, 2002.

5

Background of the Invention

[0002] This application relates to medical devices such as catheters that have sensors at their distal tips to which electrical wiring is connected.

10 [0003] Sensor catheters are used to gather information during medical procedures for diagnosing and treating patients. Ultrasonic imaging catheters, for example, may be used to gather ultrasonic images of a patient's blood vessels. Alternative imaging techniques also may be  
15 used, such as magnetic resonance imaging, optical coherence tomography and infrared imaging. During certain procedures, catheters may be used to gather a variety of physiological parameters such as temperature, pressure, pH, flow velocity and/or volumetric flow.  
20 Gradients or changes in physiological parameters across an area of interest may also be determined.

[0004] Sensor catheters are typically connected to control and analysis equipment, which may be used to generate images from raw imaging data and display physiological parameters. A number of wires must be run  
5 along the length of a typical catheter to connect the control and analysis equipment disposed at the catheter's proximal end to the sensor(s) disposed at the distal catheter tip.

[0005] In many instances, there are seven or more  
10 wires that convey power supply voltages, ground potential, drive signals, and raw sensor signals to and from the catheter sensors. These wires may be organized as a single cable bundle. However, cross-talk or noise among signal wires is a source of interference when using  
15 a sensor catheter to gather sensor measurements. This may adversely affect ringdown performance.

[0006] In view of the above, it would be desirable to provide an imaging catheter including improved wiring arrangements to reduce wire-to-wire cross-talk.

20

#### Summary of the Invention

[0007] In view of the foregoing, it is an object of the present invention to provide a sensor catheter having improved wiring arrangements for reducing wire-to-wire  
25 cross-talk.

[0008] In accordance with the principles of the present invention, sensor catheters are provided having improved wiring arrangements that reduce wire-to-wire cross-talk. The wires are grouped in distinct subgroups  
30 such as pairs of wires or groups of three or more wires that carry related signals. Accordingly, a group of seven wires may be divided into two twisted wire pairs

and one group of three twisted wires. In this manner, wire-to-wire cross-talk is reduced.

[0009] By way of example, in an ultrasonic imaging catheter, the two wires that carry sensor signals from  
5 the ultrasonic imaging catheter may be grouped together and twisted closely together as a pair. As a result, cross-talk between the two wires is reduced, especially when compared to wire arrangements in which all of the wires are arranged in a single bundle. In addition,  
10 wires associated with ultrasonic drive signals also may be grouped together as a pair. Likewise, wires carrying power supply and clock signals (e.g., for use by multiplexer circuits at the catheter's distal end) may be grouped together as a pair.

15 [0010] The above examples are merely illustrative arrangements. According to the present invention, sensor catheters having varying signaling needs and signal wires will require different wire subgroup arrangements. The resulting wire subgroup arrangements may be twisted  
20 together to form a single wire group formed of multiple wire subgroups.

[0011] Further features of the invention, its nature and various advantages will be more apparent from the accompanying drawings and the following detailed  
25 description of the preferred embodiments.

#### Brief Description of the Drawings

[0012] The above and other objects and advantages of the present invention will be apparent upon consideration  
30 of the following detailed description, taken in conjunction with the accompanying drawings, in which like reference characters refer to like parts throughout, and in which:

[0013] FIG. 1 is a side view of a previously known sensor catheter system;

[0014] FIG. 2 is a side-sectional view of the previously known sensor catheter of FIG. 1;

5 [0015] FIG. 3 is a cross-sectional view of a previously known wire bundle for a sensor catheter;

[0016] FIG. 4 is cross-sectional view of a first embodiment of a wiring arrangement for a sensor catheter constructed in accordance with the principles of the  
10 present invention;

[0017] FIG. 5 is cross-sectional view of a second embodiment of a wiring arrangement for a sensor catheter constructed in accordance with the principles of the present invention; and

15 [0018] FIG. 6 is cross-sectional view of a third embodiment of a wiring arrangement for a sensor catheter of the present invention.

#### Detailed Description of the Preferred Embodiments

20 [0019] Referring to FIG. 1, a previously known sensor catheter system 10 comprises catheter 12 including proximal end 12a attached to processing equipment 14 and distal end 12b including sensor assembly 16 comprising one or more sensors. By way of example, sensor assembly  
25 16 may includes a temperature sensor, a pressure sensor, a pH sensor, a flow velocity sensor and/or a volumetric flow sensor for measuring temperature, pressure, pH, flow velocity and flow volume. Of course, sensor assembly 16 may include sensors other than those listed above.

30 [0020] Sensor assembly 16 also may include an imaging sensor, such as an ultrasound, magnetic resonance, optical coherence tomography or infrared imaging sensor. Imaging sensors are typically used to gather images from

locations inside a patient's body during surgical and diagnostic procedures. Catheter 12 may be configured to gather images from inside a patient's blood vessels during percutaneous procedures such as cardiological or peripheral intervention. An illustrative catheter that may be used for ultrasound applications is described in commonly assigned U. S. Patent Application Serial No. 10/233,870, filed August 29, 2002.

[0021] Referring to FIG. 2, signals from sensor 16 are transmitted to and from processing equipment 14 via wire bundle 18 including a plurality of wires. Sensor assembly 16 may include an ultrasound sensor that transmits signals to processing equipment 14, which processes the signal data and displays the resulting images on a suitable display screen. Alternatively, sensor assembly 16 may include other sensors that transmit different signals to the processing equipment.

[0022] Processing equipment 14 also transmits signals that control the operation of sensor assembly 16. For example, if catheter 12 is an ultrasound imaging catheter, processing equipment 14 transmits drive signals for one or more transducer elements disposed within the sensor assembly. These drive signals cause the transducer elements to emit acoustic vibrations directed towards a target area within the patient's body.

[0023] Power supply signals and clock signals (e.g., for synchronizing the timing of circuitry within sensor assembly 16) also may be transmitted to sensor assembly 16 from processing equipment 14 via wire bundle 18. In order to improve overall system performance, it is desirable to reduce cross-talk between the different wires, regardless of the type of signal being transmitted.

[0024] Referring now to FIG. 3, a previously known wiring arrangement 20 for a sensor catheter comprises a single wire bundle having six individual wires 20a radially surrounding central wire 20b. Wiring arrangement further comprises outer sheath 21 for retaining the wires 20a and 20b. This arrangement has the advantage of being relatively compact, but suffers from a relatively high degree of wire-to-wire cross-talk.

[0025] Referring to FIG. 4, a first embodiment of a wiring arrangement for sensor catheter 12 constructed in accordance with the principles of the present invention is described. Wiring arrangement 22 comprises first wire bundle 24 contained within sheath 25, second wire bundle 26 contained within sheath 27 and third wire bundle 28 contained within sheath 29. First wire bundle 24 includes wires 24a and 24b, which are twisted together to assist in electrically isolating the wires from the environment, thereby reducing electromagnetic signal interference among the individual wires. Similarly, second wire bundle 26 includes wires 26a and 26b that are twisted together; third wire bundle 28 includes wires 28a, 28b and 28c that are twisted together. All three wire bundles 24, 26 and 28 are twisted together to form wiring arrangement 22 and housed within outer sheath 30.

[0026] Referring to FIG. 5, a second embodiment of a wiring arrangement for sensor catheter 12 constructed in accordance with the principles of the present invention is described. Wiring arrangement 32 comprises first wire bundle 34 contained within sheath 35, second wire bundle 36 contained within sheath 37 and third wire bundle 38 contained within sheath 39. First wire bundle 34 includes wires 34a and 34b, which are twisted together to assist in electrically isolating the wires from the

environment, thereby reducing electromagnetic signal interference among the individual wires. Similarly, second wire bundle 36 includes wires 36a and 36b that are twisted together; third wire bundle 38 includes wires  
5 38a, 38b and 38c that are twisted together. Unlike the embodiment of FIG. 4, wire bundles 34, 36 and 38 of the embodiment of FIG. 5 are not twisted and retained within an outer sheath.

[0027] Referring to FIG. 6, a third embodiment of a  
10 wiring arrangement for sensor catheter 12 of the present invention is described. Wiring arrangement 42 comprises first wire bundle 44 contained within sheath 45, second wire bundle 46 contained within sheath 47 and third wire bundle 48 contained within sheath 49. The first pair of  
15 wires includes wires 44a, 44b and 44c, which are twisted together to assist in electrically isolating the wires from the environment, thereby reducing electromagnetic signal interference among the individual wires. Similarly, second wire bundle 46 includes wires 46a, 46b  
20 and 46c that are twisted together; third wire bundle 48 includes wires 48a, 48b and 48c that are twisted together. All three wire bundles 44, 46 and 48 are twisted together to form wiring arrangement 42 and contained within an outer sheath 50.

25 [0028] Twisting the wires in the wire bundles has been observed to reduce electromagnetic interference among the wires. In some embodiments, the wires are twisted in a clockwise direction, while in others the wires may be twisted in a counter-clockwise direction. Alternatively,  
30 wires within different bundles may be twisted in different directions depending upon the application of the sensor catheter. Moreover, multiple wire bundles may be twisted together to form a single wire group. When

forming a single wire group from multiple wire bundles, the direction of wire bundle twisting preferably is opposite to the direction in which individual wires are twisted when forming the multiple wire bundles.

5   **[0029]**     The wiring arrangements of FIGS. 4-6 are merely illustrative. As would be appreciated by those of skill in the art, many different wiring arrangements are possible without departing from the scope of the present invention. For example, the wiring arrangement may  
10 include 2 or more wire bundles, each wire bundle including two or more individual wires.

**[0030]**     Although preferred illustrative embodiments of the present invention are described above, it will be evident to one skilled in the art that various changes  
15 and modifications may be made without departing from the invention. It is intended in the appended claims to cover all such changes and modifications that fall within the true spirit and scope of the invention.